

# MS3780 Fusion

## Omnidirectional Laser Scanner

Honeywell's MS3780 Fusion™ is an affordable hand-held omnidirectional laser scanner with single-line capability that increases retail checkout system efficiency with its automatic in-stand operation, optionally integrated EAS, and industry-leading scan performance.

Fusion combines omnidirectional and single-line laser bar code scanning into a lightweight, ergonomic hand-held form factor. The 20-line scan pattern provides superior scanning over existing single-line hand-held scanners making Fusion ideal for medium-volume retailers including specialty stores, pharmacies, liquor stores, and convenience stores.

An adjustable stand with 50° of tilt and three locking positions provides flexibility for the user to position the scanner for individual comfort and optimal performance. Stabilized with a weighted metal base, the stand may also be hard-mounted to counters or walls.

Fusion also includes CodeGate®, a Honeywell patented feature used in the highly successful Voyager® series. An integrated infra-red (IR) sensor automatically activates the laser when a bar code is present. The user then properly aligns the bar code before pressing the button, transmitting the data to the host. This feature provides the ability to pass over other bar codes, selecting only the required code. No other scanner offers this much control.

Standard features such as Flash ROM, MetroSelect® and MetroSet®2 programming, and user replaceable cables protect your investment by enabling Fusion to grow with you and your application requirements.

For more information on the MS3780 Fusion omnidirectional laser scanner, please visit [www.honeywell.com/aidc](http://www.honeywell.com/aidc).



## Features

- **Primary Omnidirectional Scan Pattern:** Aggressive scanning in any orientation, increasing throughput
- **Secondary Single-Line Scan Pattern:** With a push of a button, switch to a targeted single-line for menu scanning applications
- **Automatic In-Stand Detection:** Hands-free operation for presentation scanning reduces operator fatigue
- **Sleep Mode With IR Wake Up:** Multiple sleep modes reduce power consumption, extending life and lowering cost of operation
- **PowerSave Modes/PowerSwitch:** Conserves battery life and extends uptime
- **Optional Integration of RF EAS Antenna:** Increases efficiency by simultaneously deactivating RF EAS tags and decoding bar codes

# MS3780 Fusion Technical Specifications

## Operational

|                        |  |
|------------------------|--|
| Light Source           | Visible Laser Diode 650 nm ± 10 nm                                   |
| Visual Indicators      | Blue = ready to scan; White = good read; Yellow = automatic scanning |
| Host System Interfaces | USB, RS232, Keyboard Wedge, IBM 46xx (RS485), OCIA                   |

## Mechanical

|                    |   |
|--------------------|---|
| Dimensions (LxWxH) | 189 mm x 65 mm x 73 mm (7.4" x 2.6" x 2.9") |
| Weight             | 195 g (6.9 oz)                              |

## Electrical

|                           |  |
|---------------------------|--|
| Input Voltage             | 5 VDC ± 0.25 V                         |
| Operating Power (typical) | 1.4 W (275 mA @ 5 V)                   |
| Standby Power (typical)   | 1.0 W (200 mA @ 5 V)                   |
| DC Transformers           | Class 2: 5.2 VDC @ 1 A                 |
| Laser Class               | Class 1: IEC60825-1, EN60825-1         |
| EMC                       | FCC Part 15, ICES-003, EN55022 Class B |

## Environmental

|                       |  |
|-----------------------|--|
| Operating Temperature | -20°C to 40°C (-4°F to 104°F)                      |
| Storage Temperature   | -40°C to 60°C (-40°F to 140°F)                     |
| Humidity              | 5% to 95% relative humidity, non-condensing        |
| Drop                  | Designed to withstand multiple 1.5 m (5') drop     |
| Environmental Sealing | Sealed to resist airborne particulate contaminants |
| Light Levels          | 4842 Lux (450 foot-candles)                        |

## Scan Performance

|                   |  |
|-------------------|--|
| Scan Pattern      | Omnidirectional: 5 fields of 4 parallel lines; Button activated single line  |
| Scan Speed        | Omnidirectional: 1,333 scan lines per second; Single line: 67 scan lines per second  |
| Print Contrast    | 35% minimum reflectance difference   |
| Pitch, Skew       | 60°, 60°   |
| Decode Capability | Reads standard 1D and GS1 DataBar symbologies. Visit <a href="http://www.honeywell.com/aidc/symbologies">www.honeywell.com/aidc/symbologies</a> for details. |
| Warranty          | 3 year factory warranty  |



### For more information:

[www.honeywell.com/aidc](http://www.honeywell.com/aidc)

### Honeywell Security & Data Collection

Honeywell Scanning & Mobility  
90 Coles Road  
Blackwood, NJ 08012  
856.228.8100  
[www.honeywell.com](http://www.honeywell.com)

| Typical Performance*  |                               |
|---|-------------------------------|
| Narrow Width  | Depth of Field                |
| 5.2 mil   | 44 mm - 108 mm (1.8" - 4.3")  |
| 7.5 mil   | 25 mm - 190 mm (1.0" - 7.5")  |
| 10.4 mil  | 25 mm - 240 mm (1.0" - 9.5")  |
| 13 mil  | 25 mm - 280 mm (1.0" - 11.0") |
| 21 mil  | 25 mm - 300 mm (1.0" - 12.0") |
| *Resolution: 5 mil (0.127 mm)   |                               |
| *Performance may be impacted by bar code quality and environmental conditions |                               |

# Honeywell